# QUICK CX

## >SPORT. UTILITY.

On-road efficiency meets off-road ruggedness. From the fire roads of Big Sur to the cobbles of SoHo, the **Quick CX's** mountain-bike inspired frame, 700c knobby tires, front suspension, and disk brakes make it the perfect vehicle for dirt road adventuring, off-road shortcuts through the park or all-weather commuting.



### QUICK CX 1

FRAME	QUICK CX HEADSHOK, OPTIMIZED 6061 ALLOY, SAVE
FORK	HEADSHOK FATTY DL50, 50MM W/ LOCKOUT, OPI
TIRES	KENDA HAPPY MEDIUM, 700X35C

CRANKS	SHIMANO M521, 48/36/26	
DERAILLEURS R/F	SHIMANO SLX / ALIVIO	
SHIFTERS	SHIMANO DEORE	

BRUSHED	ALUMINUM.	<b>GLOSS</b>	(RAW)

HANDLEBAR/STEM	CANNONDALE C3
BRAKES	MAGURA MT2 HYDRAULIC DISC
SIZES	S, M, L, X, J

#### >RUGGED FORKS

For off-road control and on-road comfort, most **Quick CXs** are equipped with 50mm-travel, 1.5" steerer suspension forks, including the radically light and stiff **HeadShok DL50**.

#### > DISK BRAKES

Disk brakes add all-weather braking power and control.

#### RACK AND FENDER READY

With rack and fender mounts, including low-rider fork mounts, the **Quick CX** is ready for anything from commuting to fully loaded overnight adventures.

See also Althea

		QUICK CX				
	SPECIFICATIONS	SMALL	MEDIUM	LARGE	X-LARGE	JUMB0
A	SEAT TUBE LENGTH OVERALL (CM/IN)	44/17.3	48/18.9	52/20.5	56/22.0	60/23.6
В	TOP TUBE HORIZONTAL (CM/IN)	55/21.7	57/22.4	58.5/23.0	60/23.6	62/24.4
C	TOP TUBE ACTUAL (CM/IN)	53.3/20.1	54.7/21.5	56.1/22.1	57.6/22.6	59.9/23.6
D	HEAD TUBE ANGLE (DEGREES)	69°	69°	70°	70.5°	71.5°
	SEAT TUBE ANGLE (DEGREES)	74°	73.5°	73°	73°	72.5°
Ē	STANDOVER - HEADSHOK (CM/IN)	79.6/31.3	80.9/31.8	82.5/32.5	85.7/33.7	87.3/34.4
	STANDOVER - SUSPENSION (CM/IN)	80.6/31.7	82.5/32.5	84.6/33.3	86.7/34.1	88.9/35.0
	STANDOVER - RIGID (CM/IN)	77.3/30.4	79.1/31.1	81.3/32.0	83.4/32.8	85.6/33.7
3	HEAD TUBE LENGTH - HEADSHOK (CM/IN)	11.4/4.5	*	*		
ì	HEAD TUBE LENGTH - SUSPENSION (CM/IN)	14/5.5	15/5.9	16/6.3	17/6.7	18/7.1
ì	HEAD TUBE LENGTH - RIGID (CM/IN)	16/6.3	17/6.7	18/7.1	19/7.5	20/7.9
ł	WHEELBASE (CM/IN)	107.2/42.2	108.8/42.8	108.8/42.8	109.8/43.2	110.2/43.4
	FRONT CENTER	62.2/24.5	63.8/25.1	63.8/25.1	64.8/25.5	65.2/25.7
	CHAIN STAY LENGTH (CM)	45/17.7	*	*		
(	BOTTOM BRACKET DROP (CM)	6.7	*	*		
	BOTTOM BRACKET HEIGHT (CM)	33.2	*	*		
N	FORK RAKE (CM)	4.5	*	*		
V	TRAIL (CM)	8.7	8.7	8.1	7.7	7.1

